SILEX+

THE MODEL WITHOUT COMPROMISE, IN PLATINUM VERSION

SILEX+ offers all the advantages of SILEX and is equipped with our exclusive PLATINUM® treatment for long-lasting protection against fogg and scratch. In order to cover all activities requiring alternating high and low light exposure, SILEX+ is available in a CSP version, a technology that also effectively fights against blue light. Protection, Comfort and... Style, SILEX+ is available with new branch colour combinations.



- **+** ♦ PLATINUM COATING
- **+** ULTRA-WRAPAROUND FRAME
- **+** PC/TPR CO-INJECTED TEMPLES FOR GREATER COMFORT
- **+** PANORAMIC FIELD OF VISION
- **+** NO METAL PARTS

30g

+FLEX 160° TEMPLES



PSPRUS+-S01 (option)

THE MODEL WITHOUT COMPROMISE, IN 💸 PLATINUM VERSION

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
SILEX+	Clear	SILEXPPSI	2C-1,2 😭 1 FT KN C€		Anti-scratch/Anti-fog⁺ 7
	Smoke	SILEXPPSF	5-3,1 😭 1 FT KN €€		Anti-scratch/Anti-fog ⁺ P
	CSP	SILEXPCSP	5-1,4 😭 1 FT KN €€	≅ EN 166 FT C€	Anti-scratch/Anti-fog⁺ P
	Strap only (option)	PSPRUS+-S01	-	-	-

LENS MARKING

Optical class symbols:

1. Continuous work

Mechanical strength symbols:

- F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s Maximum protection for glasses.
- T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

Others symbols:

- K. Resistance to surface damage by fine particles
- N. Resistance to fogging

TECHNOLOGIES

This innovating coating is an effective solution for all activities that alternate exposure to bright light and low light, while also being suitable for extreme hot and cold temperature

environments.
CSP is also combined with the exclusive PLATINUM® coating that sustainably combats fogging.

PLATINUM

new exclusive scratch and resistant PLATINUM® coating guarantees even more safety, reliability and comfort. Washable (water and soap), this permanent coating applied on both sides of the lens makes it highly scratch resistant and durably delays the appearance of fogging.

FRAME MARKING

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

- F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s Maximum protection for glasses.
- T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

Bollé Safety product approval certificates to CE standards will be sent on request.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

PACKAGING AND EAN13 CODE							
	SILEXPPSI	SILEXPPSF	SILEXPCSP	PSPRUS+-S01			
Individual plastic bag	3660740009526	3660740009533	3660740009540	3660740007546			
10 safety spectacles per inner box	3660740109523	3660740109530	3660740109547	3660740107543			
200 safety spectacles per outer pack	3660740209520	3660740209537	3660740209544	3660740207540			

CHARACTERISTICS			
LENSES	PC - 2,2 mm - Curve 9		
FRAME	-		
TEMPLES	PC + TPR		
STRAP	Nylon/15mm/Adjustable		
SPARE LENSES	No		









Non-contractual pictures

09/03/2020

Europe Bollé Safety 34 rue de la Soie 69100 Villeurbanne - France Tél.: 00 33 (0) 4 78 85 23 64 Fax: 00 33 (0) 4 78 85 28 56 contact@bolle-safety.com

U.K. Bollé Safety Unit C83 - Barwell Business Park Leatherhead Road - Chessington Surrey - KT9 2NY - UK

Tél.: 00 44 (0)208 391 4700 Fax: 00 44 (0) 208 391 4733 e-mail: uk@bollebrands.com

