

WHE00152



INCLUDES



TECHNICAL DETAILS

STANDARD
EN 397 | 440V a.c. / -30°C / LD / MM
EN 50365 (Class 0)
CE 2008

EN 12492
for the following clauses only:
Shock energy absorption capacity
4.2.1.2 front impact, 4.2.1.3 lateral impact,
4.2.1.4 rear impact
4.2.2 | Penetration

TEMPERATURE OF USE
-30°C / +50°C

WEIGHT
490 g

SIZE
Universal-adjustable from 52 to 63 cm

MATERIAL
EXTERNAL SHELL:
HD Polypropylene

INTERNAL SHELL:
Neopor® Cycled® by BASF | EPS obtained from chemical recycling of plastic waste.

HEADBAND:
Soft PA Nylon

WHE00152-203
ORANGE

CATEGORY
III

TECHNOLOGIES

POLYPROPYLENE HD EXTERNAL SHELL
Lightweight external shell with exponential better performance. Excels in impact absorption, especially at lower temperatures (-30°C). Resists yellowing and degradation.

D-CORE TECHNOLOGY
Internal shell component designed with a low-density Neopor® Cycled® EPS inner core optimized for top impact protection.

HD CROWN PROTECTION
Durable, internal shell component composed of high-density Neopor® Cycled® EPS that provides stronger side impact absorption and inner core protection.

CLICK-IN SYSTEM
Enhanced padding attachment system that quickly secures into place and allows for easy replacement, and removal. Patented system improves padding durability.

DRY+ LINER
Advanced composite fabric integrated with Hydrocool® moisture-wicking technology and exceptionally soft textiles for enhanced user comfort.

ADAPTIVE FIT SYSTEM
Size adjustment system that adapts to head shapes to create a personalized, secure fit. Adjusting the double diameter dial allows the ergonomic side wings to cradle the back of the neck while the self-adjusting hinge moves up and down to keep the system in a comfortable and secure position that moves as the wearer moves.



ELECTRIC SHOCK PROTECTION (EN 50365)
Protection against potential contact during working with live or close to live parts on low voltage installations not exceeding 1000 V a.c. or 1500 V d.c.



ELECTRICAL INSULATION
Protection against electric hazards. Optional requirements EN 397 – 440 V.



ADVANCED ECO-LEATHER CHINSTRAP
Eco-leather chinstrap with 5 adjustment points for a personalized fit. Accommodates wider head sizes and adapts to earmuff use. Color-coded fasteners indicate EN standard compliance rating.





LATERAL ADJUSTMENT DIVIDER

Side regulator point on chinstrap for adjustment and positioning for a more tailored fit.



RING TO HOOK

Chinstrap loop that enables the wearer to securely attach the helmet to a harness or other items.



EASY CLICK SYSTEM

Helmet designed with integrated slots for easy mounting of KASK eye and face protection accessories. Easy Click Adapters required.



REPLACEABLE LAMP CLIPS

Helmet designed with 4 removable nylon external lamp attachment clips. Compatible with KASK headlamps and industry headlamps with elastic bands.



FRONT ATTACHMENT POINT

Front attachment point for advanced customization and easy integration of accessories such as badge holders and headlamps. Includes cap cover for debris protection.



EARMUFF ATTACHMENT SLOTS

Helmet designed with standard 30 mm EURO slots for attaching KASK earmuffs.



EARPLUG HOOKS

Lamp clip feature that holds corded earplugs.



HI-VIZ NAMEPLATE

Designed with a high visibility nameplate for easy identification on the back of the helmet.

PERFORMANCES

Protection against top impacts	K	5 Kg from 1 m 100 J
Protection against front, lateral and rear impacts	K	5 Kg from 0,5 m 25 J
Protection against penetration of objects	K	3 Kg from 1 m 30 J
Chinstrap release	K	>15 kg <25 kg

K EN 397 standard requirements

K Additional tests in conformity with EN 12492 requirements

K EN 397 optional requirements

Protection against electric shock	K	440 V
Lower temperature resistance test	K	T= -30°C
Protection against side deformation	K	LD
Protection against molten metal splashes	K	MM

SC2 EARMUFFS

WHP00005



STANDARD
EN 352-3
ANSI S3.19



CATEGORY
III



MATERIAL
EAR CUPS AND SPACER: ABS thermoplastic
FOAM LINER: Polyether



WEIGHT
320 g



SNR (EN 352-3)
29 dB (A)
H 31 dB - M 27 dB - L 20 dB



STANDARD
30 mm SLOT



COLOR CODED
PERFORMANCE
LEVEL



EASY SIZE
ADJUSTMENT



NON-
CONDUCTIVE



CERTIFIED FOR
USE WITH KASK
HELMETS

ZEN METAL MESH VISOR

WVI00046



STANDARD
EN ISO 16321 1:2022
/A1:2025
EN ISO 16321-1:2022
EN ISO 16321-3:2022



ANSI Z87.1



MATERIAL
Metal



LENGTH
190 mm



WEIGHT
140 g



CATEGORY
II



ENHANCED OPTICAL PERFORMANCE



DEBRIS
PROTECTION



COMPATIBLE WITH
GLASSES



MICRO-
VENTILATION



HEXAGONAL
MESH

ADDITIONAL INFORMATION

GUARANTEE

3 years starting from the date of purchase.

LIFE SPAN

10 years starting from the date of manufacture. The helmet must be checked regularly and before each use to detect the presence of any damage such as cracks, detachments, deformities, or peeling that represent factual elements of the state of deterioration of the helmet. Helmets that have suffered a severe impact shall be replaced even if they do not show obvious signs of damage.

3
YEARS
GUARANTEE

10
YEARS
LIFE SPAN



SCAN FOR
COMPLETE
COLLECTION