

WV100040



Fire-resistant, scratch-resistant, and anti-fog polycarbonate full face protection. Requires KASK Easy Click Adapters FR. Can be worn with corrective glasses.


Compatible with KASK Zenith X, Primero and Quantum helmet series.

The ZEN FF PLUS VISOR mounted on the QUANTUM helmet, via the EASY CLICK ADAPTERS FR, makes the helmet usable for use in wildland firefighting (EN16471) and technical rescue activities (EN16473) where there is potential exposure to flames.


MOUNTING PARTS




TECHNICAL DETAILS




**STANDARD**  
EN ISO 16321  
EN 14458  
**CE** 2754  
ANSI Z87.1




**CATEGORY**  
III



**ENHANCED OPTICAL PERFORMANCE**  
1



**MATERIAL**  
Polycarbonate



**WEIGHT**  
145 g

TECHNOLOGIES



**PANORAMIC LENS**  
Developed to maximize visibility with minimal viewing distortion.



**ANTI-FOG**  
Equipped with an anti-fog treatment to increase wearer visibility when active and in a variety of conditions.



**ABRASION AND SCRATCH RESISTANCE**  
Lens treatment designed with protection from abrasion and scratches or increased durability and viewing clarity.



**COMPATIBLE WITH GLASSES**  
Designed for use over corrective glasses.



**DRIP PROOF UPPER CONTOUR**  
Rubber edge protects eyes from liquid and debris from entering the visor.



**EASY CLICK ADAPTERS**  
Adapters designed to be easily attached and removed to KASK eye and face protection accessories.

CE MARKINGS

CODE	COLOR	MARKING
WV100040-500	CLEAR	CE 2754   EN14458:2018   KASK   ZEN FF PLUS   MM/YY   +R1   BT   E1/E3   2C-1,2   -30°C +50°C   GL2   ET   1   -5°C +55°C   K   N   CH   9   16321   KASK   ET   1-M   -5°C +55°C   3   CH   9
WV100040-510	SMOKE	CE 2754   EN14458:2018   KASK   ZEN FF PLUS   MM/YY   +R1   BT   E1/E3   5-1,4   -30°C +50°C   GL2   ET   1   -5°C +55°C   K   N   CH   9   16321   KASK   ET   1-M   -5°C +55°C   3   CH   9
WV100040-520	SILVER MIRROR	CE 2754   EN14458:2018   KASK   ZEN FF PLUS   MM/YY   +R1   BT   E1/E3   5-2,5   -30°C +50°C   GL2   ET   1   -5°C +55°C   K   N   CH   9   16321   KASK   ET   1-M   -5°C +55°C   3   CH   9

ANSI MARKINGS

CODE	COLOR	MARKING
WV100040-500	CLEAR	ANSI Z87   +   U6   X   D3
WV100040-510	SMOKE	ANSI Z87   +   U6   L1.5   X   D3
WV100040-520	SILVER MIRROR	ANSI Z87   +   U6   L2   X   D3

ADDITIONAL INFORMATION


**GUARANTEE**  
3 years starting from the date of purchase.

**LIFE SPAN**  
10 years starting from the date of manufacture. Life span depends on various factors that can cause deterioration such as sudden temperature changes, the amount of exposure to direct sunlight and the intensity of use. Altered vision and scratches are elements that signal the need to check for deterioration of the visor.

**CLEANING**  
Clean only with water and mild soap. Allow to air dry. Do not use chemical detergents, solvents, petrol powders as they are too aggressive and could lower the structural resistance of the visor.

**3 YEARS GUARANTEE**

**10 YEARS LIFE SPAN**



SCAN FOR COMPLETE COLLECTION