WHE00132-208

WHE00132-209

WHE00132-210

WHE00132-214

WHE00132-215 LIGHT GREY

BLACK

ZENITH X MAX AIR CE



WHE00132











WHE00132-201 WHITE

WHE00132-202

WHE00132-203

WHE00132-204

WHE00132-205

WHE00132-206 BRITISH GREEN

ORANGE

GREEN

TECHNICAL DETAILS



STANDARD

EN 397 I -30°C / LD / MM



EN 12492

for the following clauses only: Shock energy absorption capacity 4.2.1.2 front impact, 4.2.1.3 lateral impact,

4.2.1.4 rear impact

4.2.2 | Penetration

4.1.4 | Ventilation



TEMPERATURE OF USE

-30°C / +50°C



WEIGHT

570 g



Adjustable – from 60 to 66 cm



MATERIAL

EXTERNAL SHELL: HD Polypropylene



INTERNAL SHELL:

Neopor® Ccycled® by BASF | EPS obtained from chemical recycling of plastic waste.







TECHNOLOGIES



HD POLYPROPYLENE EXTERNAL SHELL

Lightweight external shell with exponential better performance. Excels in impact absorption, especially at lower temperatures (-30°C). Resists yellowing and degradation.



VENTILATION CHANNELS

Helmet designed with 8 air intakes that maximize internal airflow through outflow channels providing exceptional helmet breathability.



D-CORE TECHNOLOGY

Internal shell component designed with a low-density Neopor® Ccycled® EPS inner core optimized for top impact protection.



DRY+ LINER

Advanced composite fabric integrated with Hydrocool® moisture-wicking technology and exceptionally soft textiles for enhanced user comfort.



HD CROWN PROTECTION

Durable, internal shell component composed of high-density Neopor® Ccycled® EPS that provides stronger side impact absorption and inner core protection.



Enhanced padding attachment system that quickly secures into place and allows easy replacement and removal. Patented system improves padding durability.



ADAPTIVE FIT SYSTEM

Patented size adjustment system that adapts to head shapes to create a personalized, secure fit. Adjusting the double diameter dial allows the ergonomic side wings to cradle the back of the neck while the self-adjusting hinge moves up and down to keep the system in a comfortable and secure position that moves as the wearer moves.



ADVANCED ECO-LEATHER CHINSTRAP

Eco-leather chinstrap with 5 adjustment points for a personalized fit. Accommodates wider head sizes and adapts to earmuff use. Color-coded fasteners indicate EN standard compliance rating.













ZENITH X MAX AIR CE





LATERAL ADJUSTMENT DIVIDER

Side regulator point on chinstrap for adjustment and positioning for a



FRONT ATTACHMENT POINT

Front attachment point for advanced customization and easy integration of accessories such as badge holders and headlamps. Includes cap cover for debris protection.



RING TO HOOK

Chinstrap loop that enables the wearer to securely attach the helmet to a harness or other items.



EARMUFF ATTACHMENT SLOTS

Helmet designed with standard 30 mm EURO slots for attaching KASK hearing protection earmuffs.



EASY CLICK SYSTEM

Helmet designed with integrated slots for easy mounting of KASK eye $\,$ and face protection accessories. Easy Click Adapters required.



EARPLUG HOOKS

Helmet equipped with lamp clip feature that holds corded earplugs for



REPLACEABLE LAMP CLIPS

Helmet designed with 4 removable nylon external lamp attachment clips. Compatible with KASK headlamps and other headlamps with elastic bands.



NECK PROTECTOR SLOT

3 rear helmet slots for mounting KASK Neck Protection products.



HI-VIZ NAMEPLATE

Designed with a high visibility nameplate for easy identification on the back of the helmet.

PERFORMANCES

| Protection against top impacts | K | 5 Kg from 1 m 100 J |
|--|---|-------------------------|
| Protection against front, lateral and rear impacts | K | 5 Kg from 0,5 m 25 J |
| Protection against penetration of objects | K | 3 Kg from 1 m 30 J |
| Chinstrap release | K | >15 kg <25 kg |

| Lower temperature resistance test | K | T= -30°C |
|--|---|----------|
| Protection against side deformation | K | LD |
| Protection against molten metal splashes | K | MM |

- K EN 397 standard requirements
- Additional tests in conformity with EN 12492 requirements
- K EN 397 optional requirements



Since 2019, every KASK helmet made has been tested with the KASK Rotational Impact WG11 Test. All KASK helmets have BrIC values < 0.39.

ADDITIONAL INFORMATION

GUARANTEE

3 years starting from the date of purchase.

10 years starting from the date of manufacture. The helmet must be checked regularly and before each use to detect the presence of any damage such as cracks, detachments, deformities, or peeling that represent factual elements of the state of deterioration of the helmet. Helmets that have suffered a severe impact shall be replaced even if they do not show obvious signs of damage.

Clean the helmet with the KASK Helmet cleaner or with water, neutral pH soap and a soft, clean cloth. The inner lining should be washed by hand in cold water or in the washing machine (max 30°C - 85°F). The KASK Liner Refresher is available to neutralise unpleasant odours.

The helmet should be stored away from direct sunlight or source of heat. We recommend the use of the KASK drawstring helmet bag to protect the helmet when not in use.

ADHESIVE APPLICATION

Do not apply adhesives, stickers or use paint and solvents on the helmet that do not comply with the manufacturer's specifications. Any alteration or intervention may impair its protective function.

YEARS











