

BAXTER POL

COMFORT AND INGENUITY

Baxter offers absolute comfort thanks to its ultra-wraparound frame. Designed for sunny environments, this polarized version of the BAXTER guarantees effective protection against impact and glare.



53 g

SUPPLIED WITH

Microfibre pouch
ETUIFS



BAXPOLWFS






Kit Foam + strap (option)
BAXKITFS

- + SIDE SHIELDS
- + WRAP-AROUND AND LIGHTWEIGHT FRAME
- + SPORTY DESIGN
- + POLARIZED TECHNOLOGY

bolle
SAFETY

BAXTER POL

COMFORT AND INGENUITY

| MODEL | VERSIONS | REFERENCES | LENS MARKING | FRAME MARKING | COATINGS |
|--------------------|--|------------|--|--|----------|
| BAXPOLWFS |  POLARIZED | BAXPOLWFS | 5-3,1  1 FT CE |  EN166 FT CE | AS |
| Accessories | Microfibre pouch (supplied with) | ETUIFS | - | - | - |
| | Kit Foam + strap (optional) | BAXKITFS | - | - | - |

Clear, smoke and CSP spare lens available on demand. Consult your sales representative for more information.

LENS MARKING


Optical class symbols:

1. Continuous work

Mechanical strength symbols:

- F.** Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s
Maximum protection for glasses.
- T.** The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.
- B.** Medium energy impact, resists a 6 mm, 0.86 g ball at 120 m/s

Others symbols:

CE European standard  Manufacturer name


TECHNOLOGIES

POLARIZED

A technology approved for permanent wear and certified with perfect optical quality, it offers unbeatable comfort by filtering glare and reflections. Ideal for the maritime environment. Filters 99.99% of UVA/UVB.

FRAME MARKING

EN 166: guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

3. Liquid droplets.
 4. Large dust particles > 5 microns.
 5. Gas and fine dust particles < 5 microns.
- F.** Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s. Maximum protection for glasses.
- T.** The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.
- B.** Medium energy impact, resists a 6 mm, 0.86 g ball at 120 m/s
- CE** European standard  Manufacturer name

Bollé Safety product approval certificates to CE standards will be sent on request.

CLEANING AND STORAGE

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfibre pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

PACKAGING AND EAN13 CODE

| | BAXPOLWFS | BAXKITFS |
|--------------------------------------|---------------|---------------|
| Individual plastic bag | 3660740009502 | 3660740008000 |
| 10 safety spectacles per inner box | 3660740109509 | 3660740108007 |
| 240 safety spectacles per outer pack | 3660740209506 | 3660740208004 |

CHARACTERISTICS

| | |
|----------------|------------------------------|
| LENSES | PC - 2,2 mm - Curve 8 |
| FRAME | PC |
| TEMPLES | PC |
| STRAP | Nylon |



30/06/2020

Europe Bollé Safety
34 rue de la Soie
69100 Villeurbanne - France
Tél. : 00 33 (0) 4 78 85 23 64
Fax : 00 33 (0) 4 78 85 28 56
contact@bolle-safety.com

bolle-safety.com

U.K. Bollé Safety
Unit C83 - Barwell Business Park Leatherhead Road - Chessington
Surrey - KT9 2NY
Tél. : 00 44 (0)208 391 4700
Fax : 00 44 (0)208 391 4733
e-mail : uk@bollebrands.com

bolle
SAFETY