# CONTOUR RX







23 g

SUPPLIED WITH

Hard case, microfibre cloth, cord



FRAME

"Plastic" Polycarbonate LENS MATERIAL AVAILABLE

Polycarbonate



- **EXECUTE** COMFORTABLE, STRAIGHT TEMPLES
- **+** SIDE SHIELDS
- **H** NON-SLIP BRIDGE



# CONTOUR RX

MODEL	VERSIONS	REFERENCES	SIZE	FRAME MARKING	TEMPLE LENGTH
CONTOUR RX	PC / Gun metal	CONTN	68/16	<b>≅</b> EN166 F C€	121 mm

## LENS MARKING

Lens available in clear, 3 shades of gray and 3 shades of smoke.

### Polycarbonate lens:

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s Maximum protection for glasses.

Maximum sphere power +7/-6

Maximum cylinder compared with sphere: +/-5

## CORRECTED BASE:

Corrected base: 8

PACKAGING AND EAN13 CODE			
	CONTN		
Per piece	3660740000127		

# FRAME MARKING

### **EN 166**

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s Maximum protection for glasses.

European standard

Bollé safety product approval certificates to CE standards will be sent 6h request.

CLEANING: The lenses should be cleaned regularly. Bollé Safety recommends only using

**MAINTENANCE:** Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

CHARACTERISTICS		
Polycarbonate		
Single vision - Progressive		
PC / Gun metal		
Non applicable		
Non applicable		









29/09/2017

Europe Bollé Safety 95 rue Louis Guérin 69100 Villeurbanne - France Tél.: 00 33 (0) 4 78 85 23 64 Fax: 00 33 (0) 4 78 85 28 56 contact@bolle-safety.com

U.K. Bollé Safety Unit C83 - Barwell Business Park Leatherhead Road - Chessington Surrey - KT9 2NY

Tél.: 00 44 (0)208 391 4700 Fax: 00 44 (0)208 391 4733 e-mail: sales@bolle-safety.co.uk

