

KICK

HIGH-PROTECTION, STYLISH AND COLOURFUL DESIGN!

Bollé Safety eyewear is ideal for a variety of applications from construction sites through to industry. Our latest innovation is a range of safety glasses with prescription lenses in stylish, colourful frames.

KICK and SPICY come in two unisex models, one with impact-resistant side shields for use in industry and the other with robust design for the office.

**PRESCRIPTION
FRAME**
★ EXCELLENCE



KICMBKO



KICSDTO



KICMBKGY



17 g

SUPPLIED WITH

Hard case,
microfibre cloth

FRAME

• TRNZZ/TPR

LENS MATERIAL AVAILABLE

• CR39
• Polycarbonate



- + BUILT-IN SIDE SHIELDS**
- + EN166 LOW ENERGY IMPACT RESISTANCE - F MARKING**
- + CHOICE OF 3 COLOURS - UNISEX**
- + AVAILABLE WITH ALL TYPES OF LENSES**
- + AVAILABLE WITH ALL THE COATINGS IN THE EXCELLENCE PRESCRIPTION RANGE**

bollé
SAFETY

KICK

HIGH-PROTECTION, STYLISH AND COLOURFUL DESIGN!

MODEL	REFERENCES	VERSIONS	SIZE	FRAME MARKING	TEMPLE LENGTH
KICK	KICMBKO	Black/Orange	54/19	EN166 F CE	140 mm
	KICSDTO	Dark tortoise	54/19	EN166 F CE	140 mm
	KICMBKGY	Black/Grey	54/19	EN166 F CE	140 mm

LENS MARKING

Polycarbonate lens:

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s
Maximum protection for glasses.

CR39 lens:

S. Extra strong, resists a 22 mm 43 g ball falling 1.30 m at 5,1 m/s.

FRAME MARKING

EN 166 : guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s
Maximum protection for glasses.

CE European standard  Manufacturer name

Bollé safety product approval certificates to CE standards will be sent on request.

STANDARD ASSEMBLY RESTRICTIONS:

Maximum sphere power: +10/-10

Maximum cylinder compared with sphere : +/-6.

CORRECTED BASE:

Corrected base : 4

CLEANING AND STORAGE

CLEANING : The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

MAINTENANCE : Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

STORAGE : All products must be stored in a dry and clean environment.

PACKAGING AND EAN13 CODE

	KICMBKO	KICSDTO	KICMBKGY
Per piece	3660740008970	3660740008994	3660740008987

CHARACTERISTICS

LENS MATERIALS	CR39, Polycarbonate
TYPES OF CORRECTIONS AVAILABLE	Single vision - Bifocal - Progressive - Degressive
FRAME MATERIAL	TRNZZ/TPR



08/03/2019

Europe Bollé Safety
34 rue de la Soie
69100 Villeurbanne - France
Tél. : 00 33 (0) 4 78 85 23 64
Fax : 00 33 (0) 4 78 85 28 56
contact@bolle-safety.com

bolle-safety.com

U.K. Bollé Safety
Unit C83 - Barwell Business Park Leatherhead Road - Chessington
Surrey - KT9 2NY
Tél. : 00 44 (0)208 391 4700
Fax : 00 44 (0)208 391 4733
e-mail : uk@bollebrands.com

bolle
SAFETY