

# MERCURO

## 100% OUTDOOR

Stylish safety glasses with a wrap-around design, PVC nose bridge and bi-material temples for added comfort. Mercurio's bold styling coupled with Platinum® anti-scratch/anti-fog coating provides maximum protection and performance that exceeds expectations.



 PLATINUM®



MERCSP



MERPSF



MERPOL

SUPPLIED WITH

Microfiber pouch  
ETUIFS  
(for MERPOL only)




32g



MERPSF + RUSHKITS














RUSHKITS (option)  
Strap

- + ULTRA-WRAPAROUND FRAME // LARGE FIELD OF VISION
- + NO METAL PART
- + PC/TPR CO-INJECTED TEMPLES FOR GREATER COMFORT
- +  PLATINUM® (+P) SCRATCH AND FOG RESISTANT COATING – EXCEPT FOR POLARIZED VERSION
- + NON-SLIP NOSE BRIDGE
- + SPORTY DESIGN

**bolle**  
SAFETY

# MERCURO

## 100% OUTDOOR

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
MERCURO	 <b>CSP</b>	MERCSP	5-1,4  1 FT KN CE	 EN166 FT CE	Anti-scratch/Anti-fog 
	 Smoke	MERPSF	5-3,1  1 FT KN CE	 EN166 FT CE	Anti-scratch/Anti-fog 
	 <b>POLARIZED</b>	MERPOL	5-3,1  1 FT CE	 EN166 FT CE	AS
	Strap only (option)	RUSHKITS	-	-	-

### LENS MARKING

#### Optical class symbols:

1. Continuous work

#### Mechanical strength symbols:

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s  
Maximum protection for glasses.

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

#### Others symbols:

K. Resistance to surface damage by fine particles

N. Resistance to fogging


CE European standard  Manufacturer name

### FRAME MARKING

**EN 166:** guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

F. Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s  
Maximum protection for glasses.

T. The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

CE European standard  Manufacturer name

**Bollé Safety product approval certificates to CE standards will be sent on request.**

### CLEANING AND STORAGE

**CLEANING:** The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

**MAINTENANCE:** Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

**STORAGE:** All products must be stored in a dry and clean environment.

### TECHNOLOGIES

#### CSP

This innovating coating is an effective solution for all activities that alternate exposure to bright light and low light, while also being suitable for extreme hot and cold temperature environments.

CSP is also combined with the exclusive PLATINUM® coating that sustainably combats fogging.

#### PLATINUM

The exclusive scratch and fog resistant PLATINUM® coating guarantees even more safety, reliability and comfort. Washable (water and soap), this permanent coating applied on both sides of the lens makes it highly scratch resistant and durably delays the appearance of fogging.

### PACKAGING AND EAN13 CODE

	MERCSP	MERPSF	MERPOL	RUSHKITS
Individual plastic bag	3660740008901	3660740008895	3660740008888	3660740007546
10 safety spectacles per inner box	3660740108908	3660740108892	3660740108885	3660740107543
200 safety spectacles per outer pack (240 for MERPOL)	3660740208905	3660740208899	3660740208882	3660740207540

### CHARACTERISTICS

LENSES	PC - 2,2 mm - Curve 8
FRAME	PC
TEMPLES	PC + TPR
BRIDGE	PVC



Non-contractual pictures

01/10/2019

Europe Bollé Safety  
34 rue de la Soie  
69100 Villeurbanne - France  
Tél. : 00 33 (0) 4 78 85 23 64  
Fax : 00 33 (0) 4 78 85 28 56  
contact@bolle-safety.com

U.K. Bollé Safety  
Unit C83 - Barwell Business Park Leatherhead Road - Chessington  
Surrey - KT9 2NY - UK  
Tél. : 00 44 (0)208 391 4700  
Fax : 00 44 (0)208 391 4733  
e-mail : uk@bollebrands.com

[bolle-safety.com](http://bolle-safety.com)

**bolle**  
SAFETY