

# FLIP-UP FACESHIELD

## ULTRA PROTECTION & LIGHTNESS

Users will be thrilled by the lightness and design of this flip front protector. The RELPSI version is anti-fog polycarbonate with a thickness of 1.5 mm that will protect you against short circuit electric arcs.

**SUPPLIED WITH :** Protective bag

 200 G

+ **PROTECTION AGAINST ELECTRICAL SHORT CIRCUIT ARCS (RELPSI VERSION)**

+ **19 X 29 CM TILTING SHIELD**

+ **ANTI-FOG COATING DEPENDING ON THE VERSION**



### TECHNOLOGIES

PLATINUM LITE

### VERSIONS



RELPSI



RELRSI



FARELPSI



FARELRSI

**bolle**  
SAFETY



CERTIFIED  
FOR EXPLOSIVE  
ATMOSPHERES  
ATEX IIA, IIA, IIB, IIC,  
AREA 1,2,20,21,22

**FLIP-UP FACESHIELD**

| USE | VERSION          | REFERENCE | LENS MARKING        | FRAME MARKING    | COATING       | STANDARD    |
|-----|------------------|-----------|---------------------|------------------|---------------|-------------|
| ↕   | ☉ CLEAR -PC      | ■ RELPSI  | ☰ 1 F €€            | ☰ EN166 3 B 8 €€ | PLATINUM LITE | EN166-EN170 |
| ↕   | ☉ CLEAR -ACETATE | ■ RELRSI  | 2C-1.2 ☰ 2 B 8 N €€ | ☰ EN166 3 B 8 €€ | ANTI-FOG      | EN166-EN170 |
| ↕   | ☉ CLEAR -PC      | FARELPSI  | ☰ 1 F €€            |                  | PLATINUM LITE | EN166-EN170 |
| ↕   | ☉ CLEAR -ACETATE | FARELSI   | 2C-1.2 ☰ 2 B 8 N €€ |                  | ANTI-FOG      | EN166-EN170 |

BOLLÉ SAFETY PRODUCT APPROVAL CERTIFICATES TO €€ STANDARDS WILL BE SENT ON REQUEST.

**PACKAGING & EAN13 CODE**

| SINGLE:<br>Size: 24 x 18 x 9 mm | INNER BOX:<br>Size: xx cm<br>Weight: kg | OUTER PACK:<br>Size: 60 x 50 x 38 cm<br>Weight: 12.25 kg |
|---------------------------------|---|--|
| 3660740003487                   | 3660740103507 -1 pcs                    | 3660740203504 -50 pcs                                    |
| 3660740001957                   | 3660740101954 -1 pcs                    | 3660740201951 -50 pcs                                    |
| 3660740003494                   | 3660740103491 -25 pcs                   | 3660740203498 -250 pcs                                   |
| 3660740001520                   | 3660740101527 -25 pcs                   | 3660740201524 -200 pcs                                   |
| <b>CUSTOM CODE: 3926909790</b>  |   |  |



CERTIFIED FOR EXPLOSIVE ATMOSPHERES  
ATEX II, IIIA, IIIB, IIIC, AREA 1,2,20,21,22

**GENERAL SPECIFICATIONS**

|       |                      |          |  |
|-------|----------------------|----------|--|
| LENS  | POLYCARBONATE - 1 MM | FOAM     |  |
| CURVE |                      | STRAP    |  |
| FRAME | PP                   | OPTIONAL |  |



KNOW MORE ABOUT MARKINGS:

OR SCAN:

**CLEANING & STORAGE**

**CLEANING:** The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

**MAINTENANCE:** Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

**STORAGE:** All products must be stored in a dry and clean environment.



MADE IN: TW

DATASHEET: 03-29-2022

**bolle-safety.com**

**Europe Headquarters**  
34 rue de la Soie  
69100 Villeurbanne  
France  
P : 00 33 (0) 4 78 85 23 64

**U.K. & Ireland**  
Unit C83- Barwell Business Park  
Leatherhead Road - Chessington  
Surrey - KT9 2NY - UK  
P : 00 44 (0)208 391 4700

**USA Office**  
2810 Caribou Court, Suite 160  
Carlsbad, CA 92010  
United States of America  
P : 800 222 6553

**Asia-Pacific Office**  
32-40 Fairchild Street  
Heatherton VIC 3202  
Australia  
P : 1300 138 098

**THE PPE EYEWEAR SPECIALISTS**