

STANDARD

EN 397 | 440V a.c. / -30°C / LD / MM EN 50365 (Class 0)

€ 2008 **UK** 8503

EN 12492

for the following clauses only: Shock energy absorption capacity 4.2.1.2 front impact, 4.2.1.3 lateral impact, 4.2.1.4 rear impact 4.2.2 | Penetration



MATERIAL

EXTERNAL SHELL: HD Polypropylene

INTERNAL SHELL: HD Expanded Polystyrene

HEADBAND: Soft PA Nylon



TEMPERATURE OF USE

-30°C / +50°C



WEIGHT

490 g



Universal-adjustable from 52 to 63 cm



WHE00125

VVI1L00123						
O 201		204		208		21
202		205		210		21
203		206		209		



CATEGORY

TECHNOLOGIES

- **D-CORE TECHNOLOGY** Low density inner core protects from top impacts.
- > HD CROWN PROTECTION High-density inner shell protection designed for all-around impacts.
- **CLICK-IN SYSTEM** Attachment system that lets padding easily snap in and out.
- > DRY+ LINER Moisture-wicking fabric for enhanced comfort.
- **ADAPTIVE FIT SYSTEM** Size adjustment system that adapts to create a personalized, secure fit.
- > LONGER CHINSTRAP Eco-leather chinstrap with 10 cm of added length for a personalized fit.
- **ADVANCED CHINSTRAP** 5 adjustment points and EN color-coded fastener.
- > COLOR-CODED FASTENER The color of the fastener indicates the EN standard to which the chinstrap refers.
- **EASY CLICK SYSTEM** Integrated slots for eye and face protection. Adapters required.



YEARS

DISCOVER MORE



SCAN FOR COMPLETE COLLECTION









